

Supported Codecs

AVC-Intra, AVCHD, Canon XF MPEG2, Digital SLR, DV-NTSC, DV-PAL, DVCPRO50, DVCPROHD, DPX, HDV, XDCAM EX, XDCAM HD, XDCAM HD422, DNxHR & DNxHD, Apple ProRes 4444, Apple ProRes 422 HQ, Apple ProRes 422, Apple ProRes LT, Apple ProRes 422 Proxy, Uncompressed 8-bit 4:2:2, Uncompressed 10-bit 4:2:2.

Software

Software Included

Media Express, Disk Speed Test, LiveKey, Blackmagic Desktop Video Utility and Blackmagic driver on Mac OS and Windows. Media Express, Blackmagic Desktop Video Utility and Blackmagic driver on Linux.

Internal Software Upgrade

Firmware built into software driver. Software driver loads upgrades at system start or via updater software.



Adobe Photoshop CC
Other supported applications include:

The Foundry Nuke, Grass Valley Edius, Sony Catalyst Production Suite, Tools On Air Just: Play & Live & In, Softron MovieRecorder & MReplay, Adobe Flash Media Live Encoder, Telestream Wirecast, Livestream Producer, Resolume Arena, Magix Vegas Pro & Movie Edit Pro Premium, Corel VideoStudio Pro, CyberLink PowerDirector, Vidblaster X & Studio & Broadcast, Uniplay One & CG, CasparCG Server, Magicsoft CG, Xsplit Broadcaster, Imagine Communications Velocity & InfoCaster, DevTek Easy Media Suite, Metus Ingest, Boinx Software MimoLive, Cinegy Capture Pro, vMix Live, Renewed Vision ProPresenter, Ventuz Director, Class X Liveboard & Coral CG, Glookast Capturer, Open Broadcaster Software Studio, Nautilus NEMO3D, Burst Video Webclip2Go & [REC]Marker.

Video Standards

SD Video Standards 525i59.94 NTSC, 625i50 PAL

HD Video Standards

720p50, 720p59.94, 720p60 1080p23.98, 1080p24, 1080p25, 1080p29.97, 1080p30 1080PsF23.98, 1080PsF24, 1080PsF25, 1080PsF29.97, 1080PsF30 1080i50, 1080i59.94, 1080i60 **SDI Compliance** SMPTE 259M and 292M.

SDI Metadata Support RP 188/SMPTE 12M-2 and closed captioning.

Audio Sampling

Television standard sample rate of 48 kHz and 24 bit.

SDI Color Precision 8-bit & 10-bit YUV 4:2:2.

SDI Video Sampling 4:2:2 Color Space REC 601, REC 709.

HDMI Video Sampling 4:4:4, 4:2:2 & 4:2:0

HDMI Configuration HDMI automatically configures to connected display. HDMI Resolution Pixel for pixel HD resolution input to connected device.

HDMI Color Precision 10-bit.

Multiple Rate Support

HDMI and SDI video connections are switchable between standard definition and high definition.

Processing

Colorspace Conversion

Hardware based real time.

HD to SD Down Conversion

Software based down conversion during video playback.

HD Cross Conversion

Software based cross conversion from 720p to 1080HD on playback.


Real Time Effects


DaVinci Resolve, Final Cut Pro X internal effects. Premiere Pro CC Mercury Playback Engine effects. Avid Media Composer internal effects.

Physical Installation

Requires computer with a Thunderbolt™ port. Please check the Support pages to see the full system requirements.

Physical Specifications







Mac 10.13 High Sierra, Mac 10.14 Mojave or later.



Windows 7, 8.1 and 10, all 64-bit.



oz

Power Requirements		
Powered by Thunderbolt cable.		
EMC Certifications		
FCC, CE and C-Tick.		
Environmental Specifications		
Operating Temperature	Storage Temperature	Relative Humidity
5° to 40° C (32° to 104° F)	-20° to 45° C (-4° to 113° F)	0% to 90% non-condensing
What's Included		
UltraStudio Mini Monitor	SD card with software and manual	
Warranty		
12 Month Limited Manufacturer's V	Varranty.	
	e owners. MSRP includes duties, but excludes sales tax and ertise on third party websites to previous visitors to our si	
Dischmagic Dasign Authori		

Blackmagic Design Authorized Reseller