



H-PS45175 LUMIX G Teleobjektiv

Features	Lens Construction	14 elements in 10 groups (2 aspherical lenses , 2 ED lens)
	Nano Surface Coating	yes
	Mount	Micro Four Thirds mount
	Optical Image Stabilizer	YES (POWER OIS)
	Focal Length	f=45-175mm (35mm camera equivalent 90-350mm)
	Aperture Type	7 diaphragm blades / Circular aperture diaphragm
	Aperture Range	F4.0(Wide) - F5.6(TELE)
	Minimum Aperture	F22
	Closest Focusing Distance	0.9m / 3.0ft
	Maximum magnification	Approx. 0.2x / 0.4x (35mm camera equivalent)
General	Diagonal Angle of View	27°(Wide) to 7.1°(TELE)
	Filter Size	φ46mm / 1.8in
	Max. Diameter	φ61.6mm / 2.4in
	Overall Length	Approx. 90.0mm (from the tip of the lens to the base side of the lens mount) / 3.5in
	Weight [g]	Approx. 210g (excluding lens cap and lens rear cap)
	Weight [oz]	Approx. 7.4oz (excluding lens cap and lens rear cap)
Standard Accessories	Lens cap/Lens rear cap/Lens storage bag/Lens hood	
Others	Electric zoom lever/Manual focus ring/Manual zoom ring	