STANDARD



Kamera och videokamera

LUMIX G objektiv

LEICA DG-objektivet H-X1025

Features	Lens Construction	17 elements in 12 groups (3 aspherical lenses, 4 ED lenses, 1 UHR lens)
	Nano Surface Coating	-
	Mount	Micro Four Thirds mount
	Optical Image Stabilizer	-
	Focal Length	f=10-25mm (35mm camera equivalent 20-50mm)
	Aperture Type	9 diaphragm blades / Circular aperture diaphragm
	Maximum Aperture	F1.7
	Minimum Aperture	F16
	Closest Focusing Distance	0.28m / 0.92ft
	Maximum Magnification	Approx. 0.14x / 0.28x (35mm camera equivalent)
	Diagonal Angle of View	94o (Wide) - 47o (Tele)
General	Dust and Splash Resistant	Yes*
	Recommended Operating Temperature	-10oC to 40oC (14oF to 104oF)
	Filter Size	ф77mm
	Max. Diameter	ф87.6mm / 3.45inch
	Overall Length	Approx. 128mm / 5.04inch (from the tip of the lens to the base side of the lens mount)
	Weight	Approx. 690g / 24.34oz (excluding lens cap, lens rear cap and lens hood)
	Standard Accessories	Lens cap, Lens rear cap, Lens hood, Lens storage bag
NOTE	NOTE	*Dust and Splash Resistant does not guarantee that damage will not occur if this lens is subjected to direct contact with dust and water.

Copyright © 2019 Panasonic. Alla rättigheter förbehålls.